

THE BATTLE IS  
**YOURS  
FOR THE  
TAKING.**

OSI was born on the jobsite. That's how we develop tough products that reduce risk for the contractors they were built for. Because the last thing contractors would risk putting their name on is an inferior product. And neither would we.



**OSI** WHEN THE JOB GETS TOUGH

- 800-624-7767
- onthejob@ositough.com
- ositough.com
- Henkel Corporation  
One Henkel Way  
Rocky Hill, CT 06067  
Available M-F 9am-4pm EST

WITH OUR PRODUCT LINE,  
**MOTHER  
NATURE  
DOESN'T  
STAND A  
CHANCE.**



# THE MOST EXTENSIVE LINE OF HIGH PERFORMANCE SEALANTS, ADHESIVES AND FOAMS TO EVER STARE DOWN MOTHER NATURE.



**QUAD<sup>®</sup> MAX**  
Window, Door and Siding Sealant

- 5X STRETCH
- PROVEN WET SURFACE APPLICATION
- STRONG ADHESION LB
- 9.5 fl oz
- 4600+ Color Matches
- 3-in-1 exterior, interior and bedding
- GREENGUARD Certified
- Now available in CLEAR




**QUAD<sup>®</sup> FOAM**  
Window and Door Installation Foam

- LOW MED. HIGH FOAM PRESSURE/ EXPANSION
- QUICK SETTING 10 min.
- COLD TEMP. APPLICATION -14°F
- 21.1 oz, 16 oz
- Won't bow windows or doors
- Closed cell structure
- Insulation value of R5/inch
- GREENGUARD Certified



**FOAM GUN**  
Foam Applicator Gun

- 8" barrel
- Instant cut off Teflon<sup>®</sup> valve
- Detachable screw on tip for narrow openings




**FOAM CLEAN**  
Foam & Applicator Cleaner

- 12 oz
- Removes uncured polyurethane foam
- Use to clean OSI<sup>®</sup> Foam Applicator Gun
- Evaporates quickly



**QUAD<sup>®</sup> MAX Sausage Pack**  
Window, Door and Siding Sealant

- 5X STRETCH
- PROVEN WET SURFACE APPLICATION
- STRONG ADHESION LB
- 19.2 oz
- Available in White
- Same great benefits as QUAD<sup>®</sup> MAX
- Less waste on jobsite
- GREENGUARD Certified



**QUAD<sup>®</sup> FLASH Sausage Pack**  
Liquid Applied Flashing Membrane

- 20 oz
- Breathable liquid applied membrane
- All weather application
- Same day installation of windows
- UV resistant



**BUTYL FLASH**  
Butyl Window Flashing Tape

- 4", 6", 9"
- Highly durable, resists damage & tearing
- Integrates window into the opening
- Innovative foil design is UV resistant self-healing butyl technology




OSI offers color matches for 330+ window, door, siding & paint manufacturers' palettes. Find your perfect match at [OSITOUGH.COM](http://OSITOUGH.COM)




**QUAD<sup>®</sup> MAX**  
Window, Door & Siding Sealant

- 9.5 fl oz
- Proven wet surface application
- 3-in-1 exterior, interior and bedding
- GREENGUARD Certified
- Now available in CLEAR



**QUAD<sup>®</sup>**  
Window, Door & Siding Sealant

- 9.5 fl oz
- All season formula
- Dirt & dust resistant
- Proven wet surface application
- UV resistant




**QUAD<sup>®</sup> Invisible**  
Window, Door & Siding Sealant

- 9.5 fl oz
- Crystal clear formula
- Clear cartridge
- All the benefits of QUAD<sup>®</sup>



**H2U**  
Window, Door, Siding & Trim Sealant

- 10 fl oz
- Permanently flexible
- Interior/exterior use
- Superior durability
- GREENGUARD Certified



**SBR100**  
Window & Siding Caulk

- 10 fl oz
- For general purpose exterior repairs
- Paintable after cure
- Won't collect dirt or dust



**VP275**  
Multi Purpose Silicone Sealant

- 10 fl oz
- Low modulus ±50% joint movement
- 100% silicone
- Water resistant and weatherproof



**HM270**  
Silicone Sealant

- 10 fl oz
- Excellent for nonporous materials
- Easy to extrude
- Water resistant and weatherproof



**SC175**  
Draft & Acoustic Sound Sealant

- 28 fl oz
- Designed for use on sound rated wall systems
- Permanently flexible
- UL Classification R9732; UL 723



**FLAMESEAL**  
Fire, Smoke & Draft Stop Sealant

- 10 fl oz
- 1, 2, & 3 hour fire resistance rated
- Seals out fumes, smoke & water
- Fills gaps, cracks & holes



**RF140**  
Roof & Flashing Sealant

- 10 fl oz
- Excellent for general roof repairs
- Resists cracking
- Applies in cold temperatures and on wet surfaces



**GUTTER GS121**  
Gutter & Seam Sealant

- 10 fl oz & 5 fl oz
- Permanently flexible
- Seals most common gutter & downspout materials
- Cures to a tough, rubbery gasket

## ADHESIVES & FOAMS




**SF450 Heavy Duty**  
Subfloor Adhesive

- 28 fl oz
- Reduces squeaky floors
- Bridges minor framing gaps
- Strong adhesion
- Meets ASTM D3498



**SF450 20°-120°**  
Subfloor Adhesive

- 28 fl oz
- Bonds to wet, frozen & treated lumber
- Excellent extrusion between 20°f - 120°f
- Meets ASTM D3498
- GREENGUARD Certified



**SF450+ Polyurethane**  
Subfloor Adhesive

- 28 fl oz
- 2x yield/coverage
- 86 linear ft. vs. 38 linear ft.
- 1/4" pre cut nozzle
- 2x strength
- Meets ASTM D3498



**QB300**  
Multi Purpose Construction Adhesive

- 28 fl oz
- High initial grab minimizes nailing
- Interior/exterior applications
- Will not stain, bleed or blister surfaces



**FIRE BLOCK FOAM**  
Fireblocking Foam Seal

- 21.1 oz
- Inhibits the passage of fire & smoke through penetrations
- UL723 in accordance with E-84;
  - flame spread index = 5
  - smoke development = 0




**F38**  
Drywall Panel Adhesive

- 28 fl oz
- Reduces nailing up to 50%
- Bridges minor gaps in framing
- Reduces sound transmission
- GREENGUARD Certified



**F38 HEAVY DUTY**  
HD Drywall Adhesive

- 28 fl oz
- High bond strength
- Water & weather resistant
- Reduces sound transmission



**SW325**  
Heavy Duty Shear & Construction Adhesive

- 28 fl oz
- Rapid bond development; fast set, fast cure
- Bridges minor gaps in framing
- Bonds to most building materials



**RT600**  
Roof Tile Adhesive

- 10 fl oz
- Meets uplift requirements
- Produces a water and weather resistant seal
- Withstands high roof temperatures



**FRP555**  
Fiberglass Reinforced Panel Adhesive

- 1, 3.5, & 5 gal pails
- Strong, flexible bond
- Fast grab
- Minimizes panel slippage